

RCD Sockets - Switched 10mA

Passive

10
mA

Passive

Socket

- Mechanically latched (does not need resetting after a power loss)
- High intensity LED power on indicator
- Individually switched socket outputs
- Twin sockets fitted with twin earth terminals

Technical Data

Voltage	230V AC ~ 50Hz
Max operating current	13A (13A inductive)
Rated trip current	10mA
Typical trip speed	Less than 20mS (typical)
RCD contact break	Double pole
Latching	Mechanical, no need to reset after power loss (Passive)
Responsive to	Pulsating DC earth faults
Conforms to	BS 7288:1990, Amd 1 and BS 1363-2:1995 Amd 1-3
EMC Emissions	EN 55014-1:2006 & EN 55014-1:2000 inc A1:2001 & A2:2002
EMC Immunity	EN 61543:1996 inc A11:2003, A12:2005 & A2:2006



'Super Sensitive - 10mA'

Part No	Description
K21WPAPN10-C	RCD Single Switched Socket Slim profile Moulded front plate Fits standard 25mm back box
K22WPAPN10-C	RCD Twin Switched Socket Slim profile Moulded front plate Fits standard 25mm back box
K21MPAPN10-C	RCD Single Switched Socket Complete with metal backbox
K22MPAPN10-C	RCD Twin Switched Socket Complete with metal backbox

